

TECHNISCHE DATEN:

Aufbau

Hutmutter	Polyamid PA6 V-2
Dichteinsatz	TPE TPS
Zwischenstutzen	Polyamid PA6 V-2
Anschlussgewinde	metrisch, nach EN 60423

Eigenschaften

- Dichteinsatz zur Durchführung mehrerer Einzelkabel

Temperaturbereich	-20 °C / +100 °C (dynamisch) -40 °C (statisch, kurzzeitig)
Schutzart	max. IP65 wenn Kabel- $\varnothing$ = Loch- $\varnothing$
Hinweis	bitte den gewünschten Dichteinsatz angeben, z.B. 50.612 PA/4x2 Dichteinsätze - siehe unter Zubehör - Serie WJ-DM xx/zXz, Katalog Seite 203

TECHNICAL DATA:


Configuration

Dome nut	Polyamide PA6 V-2
Sealing insert	TPE TPS
Gland body	Polyamide PA6 V-2
Connecting thread	metric, as per EN 60423

Properties

- sealing insert for the installation of several single cables

Temperature range	-20 °C / +100 °C (dynamic) -40 °C (static, short term)
Protection grade	max. IP65 if cable $\varnothing$ = hole $\varnothing$
Comment	please indicate required sealing insert, e.g. 50.612 PA/4x2 sealing inserts - see under accessories - series WJ-DM xx/zXz, Catalog Page 203



Merkmale

Characteristics

Anschlussgewinde Standardlänge

Connecting thread standard length

A	L mm	SW1 mm	SW2 mm	H mm		RAL 7001 silbergrau silver grey Art.-Nr. / Part No.	RAL 7035 lichtgrau light grey Art.-Nr. / Part No.	RAL 9005 tiefschwarz jet black Art.-Nr. / Part No.
M12x1,5	8	15	15	31	100	50.612 PA/zXz	50612PA7035/zXz	50.612PA/SW/zXz
M16x1,5	8	20	20	35,5	100	50.616 PA/zXz	50616PA7035/zXz	50.616PA/SW/zXz
M20x1,5	8	24	24	36	100	50.620 PA/zXz	50620PA7035/zXz	50.620PA/SW/zXz
M25x1,5	8	29	29	43	50	50.625 PA/zXz	50625PA7035/zXz	50.625PA/SW/zXz
M32x1,5	10	36	36	50	25	50.632 PA/zXz	50632PA7035/zXz	50.632PA/SW/zXz
M40x1,5	10	46	46	51	10	50.640 PA/zXz	50640PA7035/zXz	50.640PA/SW/zXz