

TECHNISCHE DATEN:

Aufbau

Hutmutter	Polyamid PA6 V-2
Dichtring	Polychloropren-Nitrilkautschuk CR/NBR
Zwischenstutzen	Polyamid PA6 V-2
Anschlussgewinde	NPT

Eigenschaften

- Reduzier-Dichtring für kleine Kabel
- integrierte Zugentlastung
- großer Dicht- und Klemmbereich
- montagefreundlich
- UV- und Witterungsbeständigkeit gemäß UL 514B

Temperaturbereich -20 °C / +100 °C (dynamisch)
-40 °C (statisch, kurzzeitig)

Schutzart IP68 - 5 bar

Prüfnorm EN 62444 / UL 514B

UL / CSA-File E140310

Hinweis Angaben zu den Prüfergebnissen - siehe Anhang

TECHNICAL DATA:

Configuration

Dome nut	Polyamide PA6 V-2
Sealing ring	Polychloroprene-Nitrile rubber CR/NBR
Gland body	Polyamide PA6 V-2
Connecting thread	NPT

Properties

- reducing sealing ring for small cable diameter
- integrated anchorage
- wide sealing and clamping range
- easy-to-install
- UV- and weather resistance according UL 514B


Temperature range -20 °C / +100 °C (dynamic)
-40 °C (static, short term)

Protection grade IP68 - 5 bar

Test standard EN 62444 / UL 514B

UL / CSA-File E140310

Comment details about test results - see annex



Merkmale

Characteristics

Anschlussgewinde Standardlänge

Connecting thread standard length

A	ØC mm	L mm	SW1 mm	SW2 mm	H mm		RAL 7001 silbergrau silver grey			RAL 7035 lichtgrau light grey		RAL 9005 tiefschwarz jet black	
							Art.-Nr. / Part No.			Art.-Nr. / Part No.		Art.-Nr. / Part No.	
NPT 3/8"	3 - 7	15,5	22	22	44,5	100	50.138 PA/R			50.138PAR7035		50.138 PA/RSW	
NPT 1/2"	5 - 9	14,5	24	24	45	100	50.11213 PA/R			50.11213PAR7035		50.11213PARSW	
NPT 1/2"	7 - 12	15	27	27	47,5	100	50.112 PA/R			50.112PAR7035		50.112 PA/RSW	
NPT 3/4"	9 - 16	15	33	33	52	50	50.134 PA/R			50.134PAR7035		50.134 PA/RSW	
NPT 1"	12 - 20	18	42	42	60,5	25	50.110 PA/R			50.110PAR7035		50.110 PA/RSW	
NPT 1 1/4"	20 - 26	18	53	53	69,5	10	50.114 PA/R			50.114PAR7035		50.114 PA/RSW	