

TECHNISCHE DATEN:

Aufbau

Hutmutter	Polyamid PA6 V-2
Dichteinsatz	TPE TPS
Zwischenstutzen	Polyamid PA6 V-2
Anschlussgewinde	metrisch, nach EN 60423

Eigenschaften

- Dichteinsatz zur Durchführung mehrerer Einzelkabel

Temperaturbereich	-20 °C / +100 °C (dynamisch) -40 °C (statisch, kurzzeitig)
-------------------	---

Schutzart max. IP65 wenn Kabel- $\varnothing$ = Loch- $\varnothing$

Prüfnorm EN 62444

Hinweis bitte den gewünschten Dichteinsatz angeben, z.B. 50.612 PA/4x2

Dichteinsätze - siehe unter Zubehör - Serie WJ-DM xx/zXz, Katalog Seite 257

TECHNICAL DATA:

Configuration

Dome nut	Polyamide PA6 V-2
Sealing insert	TPE TPS
Gland body	Polyamide PA6 V-2
Connecting thread	metric, as per EN 60423

Properties

- sealing insert for the installation of several single cables


Temperature range	-20 °C / +100 °C (dynamic) -40 °C (static, short term)
-------------------	---

Protection grade max. IP65 if cable $\varnothing$ = hole $\varnothing$

Test standard EN 62444

Comment please indicate required sealing insert, e.g. 50.612 PA/4x2

sealing inserts - see under accessories - series WJ-DM xx/zXz, Catalog Page 257



Merkmale

Characteristics

Anschlussgewinde Standardlänge

Connecting thread standard length

A	L mm	SW1 mm	SW2 mm	H mm		RAL 7001 silbergrau silver grey			RAL 7035 lichtgrau light grey			RAL 9005 tiefschwarz jet black		
						Art.-Nr. / Part No.	Art.-Nr. / Part No.	Art.-Nr. / Part No.	Art.-Nr. / Part No.	Art.-Nr. / Part No.	Art.-Nr. / Part No.	Art.-Nr. / Part No.	Art.-Nr. / Part No.	Art.-Nr. / Part No.
M12x1,5	8	15	15	31	100	50.612 PA/zXz	50.612 PA/zXz	50.612 PA/zXz	50612PA7035/zXz	50612PA7035/zXz	50612PA7035/zXz	50.612PA/SW/zXz	50.612PA/SW/zXz	50.612PA/SW/zXz
M16x1,5	8	20	20	35,5	100	50.616 PA/zXz	50.616 PA/zXz	50.616 PA/zXz	50616PA7035/zXz	50616PA7035/zXz	50616PA7035/zXz	50.616PA/SW/zXz	50.616PA/SW/zXz	50.616PA/SW/zXz
M20x1,5	8	24	24	36	100	50.620 PA/zXz	50.620 PA/zXz	50.620 PA/zXz	50620PA7035/zXz	50620PA7035/zXz	50620PA7035/zXz	50.620PA/SW/zXz	50.620PA/SW/zXz	50.620PA/SW/zXz
M25x1,5	8	29	29	43	50	50.625 PA/zXz	50.625 PA/zXz	50.625 PA/zXz	50625PA7035/zXz	50625PA7035/zXz	50625PA7035/zXz	50.625PA/SW/zXz	50.625PA/SW/zXz	50.625PA/SW/zXz
M32x1,5	10	36	36	50	25	50.632 PA/zXz	50.632 PA/zXz	50.632 PA/zXz	50632PA7035/zXz	50632PA7035/zXz	50632PA7035/zXz	50.632PA/SW/zXz	50.632PA/SW/zXz	50.632PA/SW/zXz
M40x1,5	10	46	46	51	10	50.640 PA/zXz	50.640 PA/zXz	50.640 PA/zXz	50640PA7035/zXz	50640PA7035/zXz	50640PA7035/zXz	50.640PA/SW/zXz	50.640PA/SW/zXz	50.640PA/SW/zXz