

TECHNISCHE DATEN:
Aufbau

Hutmutter	Polyamid PA6 V-2
Dichteinsatz	TPE TPS
Zwischenstutzen	Polyamid PA6 V-2
Anschlussgewinde	Pg, nach DIN 40430

Eigenschaften

- Dichteinsatz zur Durchführung mehrerer Einzelkabel

Temperaturbereich -20 °C / +100 °C (dynamisch)
-40 °C (statisch, kurzzeitig)

Schutzart max. IP65 wenn Kabel- $\varnothing$ = Loch- $\varnothing$

Prüfnorm EN 62444

Hinweis bitte den gewünschten Einsatz angeben,
z.B. 50.009 PA/4x2

Dichteinsätze - siehe unter Zubehör -
Serie WJ-D xx/zXz, Katalog Seite 258

TECHNICAL DATA:
Configuration

Dome nut	Polyamide PA6 V-2
Sealing insert	TPE TPS
Gland body	Polyamide PA6 V-2
Connecting thread	Pg, as per DIN 40430

Properties

- sealing insert for the installation of several single cables


Temperature range -20 °C / +100 °C (dynamic)
-40 °C (static, short term)

Protection grade max. IP65 if cable $\varnothing$ = hole $\varnothing$

Test standard EN 62444

Comment please indicate required sealing insert,
e.g. 50.009 PA/4x2

sealing inserts - see under accessories -
series WJ-D xx/zXz, Catalog Page 258


Merkmale
Characteristics
Anschlussgewinde Standardlänge
Connecting thread standard length

A	L mm	SW1 mm	SW2 mm	H mm		 RAL 7001 silbergrau silver grey Art.-Nr. / Part No.  RAL 7035 lichtgrau light grey Art.-Nr. / Part No.  RAL 9005 tiefschwarz jet black Art.-Nr. / Part No.		
Pg 9	8	19	19	34	100	50.009 PA/zXz	50009P7035/zz	50.009PASWzXz
Pg 11	8	22	22	37	100	50.011 PA/zXz	50011P7035/zz	50.011PASWzXz
Pg 13,5	9	24	24	39	100	50.013 PA/zXz	50013P7035/zz	50.013PASWzXz
Pg 16	10	27	27	42,5	50	50.016 PA/zXz	50016P7035/zz	50.016PASWzXz
Pg 21	11	33	33	47,5	50	50.021 PA/zXz	50021P7035/zz	50.021PASWzXz
Pg 29	11	42	42	53	25	50.029 PA/zXz	50029P7035/zz	50.029PASWzXz