

TECHNISCHE DATEN:

Aufbau

Hutmutter	Polyamid PA6 V-2
Dichteinsatz	TPE TPS
Zwischenstutzen	Polyamid PA6 V-2
Anschlussgewinde	metrisch, nach EN 60423

Eigenschaften

Temperaturbereich	- für abgerundete Flachkabel -20 °C / +100 °C (dynamisch) -40 °C (statisch, kurzzeitig)
Schutzart	IP66 bei genauer Übereinstimmung der Kabelaußenmaße mit den Schlitzmaßen C max. (Tabelle1), IP54 im Bereich zwischen C max. und C min. (Tabelle 2)
Prüfnorm	EN 62444
Hinweis	Dichteinsätze - siehe unter Zubehör - Serie WJ-DM xxFK1


TECHNICAL DATA:

Configuration

Dome nut	Polyamide PA6 V-2
Sealing insert	TPE TPS
Gland body	Polyamide PA6 V-2
Connecting thread	metric, as per EN 60423

Properties

Temperature range	- for chamfered flat cables -20 °C / +100 °C (dynamic) -40 °C (static, short term)
Protection grade	IP66 if the outer dimensions of the cable match the slot dimensions C max. exactly (table 1), IP54 for cable dimensions between C max. and C min. (table 2)
Test standard	EN 62444
Comment	sealing inserts - see under accessories - series WJ-DM xxFK1



Merkmale

Characteristics

maximaler Klemmbereich C max.

maximal clamping range C max.

A	□ C max. mm	L mm	SW1 mm	SW2 mm	H mm		RAL 7001 silbergrau silver grey Art.-Nr. / Part No.	RAL 7035 lichtgrau light grey Art.-Nr. / Part No.	RAL 9005 tiefschwarz jet black Art.-Nr. / Part No.
M20x1,5	5 x 12	8	24	24	36	100	50.620 PA7001FK1	50.620 PA7035FK1	50.620 PASWFK1
M25x1,5	6 x 16,3	8	29	29	43	50	50.625 PA7001FK1	50.625 PA7035FK1	50.625 PASWFK1
M32x1,5	9 x 20	10	36	36	50	25	50.632 PA7001FK1	50.632 PA7035FK1	50.632 PASWFK1
M40x1,5	10 x 27	10	46	46	51	10	50.640 PA7001FK1	50.640 PA7035FK1	50.640 PASWFK1
M50x1,5	13 x 34	12	55	55	61,5	5	50.650 PA7001FK1	50.650 PA7035FK1	50.650 PASWFK1
M63x1,5	15 x 45	12	68	68	65,5	5	50.663 PA7001FK1	50.663 PA7035FK1	50.663 PASWFK1

minimaler Klemmbereich C min. IP54 im Bereich zwischen C max. und C min.

minimal clamping range C min. IP54 for cable dimensions between C max. and C min.

A	□ C min. mm	L mm	SW1 mm	SW2 mm	H mm		RAL 7001 silbergrau silver grey Art.-Nr. / Part No.	RAL 7035 lichtgrau light grey Art.-Nr. / Part No.	RAL 9005 tiefschwarz jet black Art.-Nr. / Part No.
M20x1,5	2 x 8	8	24	24	36	100	50.620 PA7001FK1	50.620 PA7035FK1	50.620 PASWFK1
M25x1,5	2 x 10	8	29	29	43	50	50.625 PA7001FK1	50.625 PA7035FK1	50.625 PASWFK1
M32x1,5	3 x 12	10	36	36	50	25	50.632 PA7001FK1	50.632 PA7035FK1	50.632 PASWFK1
M40x1,5	3 x 19	10	46	46	51	10	50.640 PA7001FK1	50.640 PA7035FK1	50.640 PASWFK1
M50x1,5	4 x 23	12	55	55	61,5	5	50.650 PA7001FK1	50.650 PA7035FK1	50.650 PASWFK1
M63x1,5	6 x 32	12	68	68	65,5	5	50.663 PA7001FK1	50.663 PA7035FK1	50.663 PASWFK1