

TECHNISCHE DATEN:

Aufbau

Hutmutter	Messing CuZn39Pb3, galv. vernickelt
Lamelleneinsatz	Polyamid PA6 V-2
Dichteinsatz	TPE TPS
Zwischenstutzen	Messing CuZn39Pb3, galv. vernickelt
O-Ring	Nitrilkautschuk NBR
Anschlussgewinde	metrisch, nach EN 60423

Eigenschaften

- Dichteinsatz ohne Bohrung
- Einsatz als Reserve-Kabelverschraubung oder als Schutz gegen Staub und Feuchtigkeit
- Dichteinsatz eignet sich zum Bohren von individuellen Durchgangslöchern

Temperaturbereich	-20 °C / +100 °C (dynamisch) -40 °C (statisch, kurzzeitig)
-------------------	---

Schutzart	IP65
Prüfnorm	EN 62444
Hinweis	Dichteinsätze - siehe unter Zubehör - Serie WJ-DM xx STO

TECHNICAL DATA:

Configuration


Dome nut	Brass CuZn39Pb3, nickel-plated
Lamellar insert	Polyamide PA6 V-2
Sealing insert	TPE TPS
Gland body	Brass CuZn39Pb3, nickel-plated
O-ring	Nitrile rubber NBR
Connecting thread	metric, as per EN 60423

Properties

- sealing insert without bore hole
- installation as spare cable gland or protection against dust and humidity
- sealing insert is suitable to bore individual clearance holes

Temperature range	-20 °C / +100 °C (dynamic) -40 °C (static, short term)
-------------------	---

Protection grade	IP65
Test standard	EN 62444
Comment	sealing inserts - see under accessories - series WJ-DM xx STO



Merkmale

Characteristics

Anschlussgewinde Standardlänge

Connecting thread standard length

A	$\frac{H}{mm}$ L mm	SW1 mm	SW2 mm	H mm		Art.-Nr. / Part No.
M12x1,5	5	14	14	25	100	50.612 M/STO
M16x1,5	5	17	17	29	100	50.616 M/STO
M20x1,5	6	22	22	33	100	50.620 M/STO
M25x1,5	7	27	27	35	50	50.625 M/STO
M32x1,5	8	34	34	42	25	50.632 M/STO
M40x1,5	8	43	43	42	10	50.640 M/STO