

TECHNISCHE DATEN:

Aufbau

Druckschraube Messing CuZn39Pb3, galv. vernickelt
Schrauben Edelstahl

Art.-Nr. 19.507M12 - 19.536M50
mit Kreuzschlitzschraube
Art.-Nr. 19.542M50 - 19.548M63
mit Schlitzschraube

Druckringe Stahl, verzinkt

Dichtring SBR/NBR, ausschneidbar

Zwischenstutzen Messing CuZn39Pb3, galv. vernickelt

Anschlussgewinde metrisch, nach EN 60423

Eigenschaften

- sehr hohe, zentrisch wirkende Zugentlastung

Temperaturbereich -30 °C / +100 °C

Schutzart IP54

Prüfnorm EN 62444

TECHNICAL DATA:

Configuration

Pressure screw Brass CuZn39Pb3, nickel-plated
Bolts Stainless steel

Part No. 19.507M12 - 19.536M50
with Phillips-recessed-head screw
Part No. 19.542M50 - 19.548M63
with slotted screw

Washers Steel, zinc-plated

Sealing ring SBR/NBR, multiple perforation

Gland body Brass CuZn39Pb3, nickel-plated

Connecting thread metric, as per EN 60423


Properties

- increased, central anchorage

Temperature range -30 °C / +100 °C

Protection grade IP54

Test standard EN 62444



Merkmale

Characteristics

Anschlussgewinde Standardlänge

Connecting thread standard length

A	ØC*	$\frac{H}{L}$	L	SW1	SW2	H		Art.-Nr. / Part No.
mm	mm	mm	mm	mm	mm	mm		
M12x1,5	5 - 8	5	14	16	29,5	100		19.507M12
M12x1,5	7 - 10	6	17	19	30	100		19.509M12
M16x1,5	8 - 12	6	20	22	32	50		19.511M16
M20x1,5	8 - 12	6	22	22	33	50		19.511M20
M20x1,5	10 - 14	7,5	22	24	33	50		19.513M20
M25x1,5	11 - 17	7,5	27	27	35,5	50		19.516M25
M25x1,5	12 - 22	8	30	34	39,5	50		19.521M25
M32x1,5	19 - 30	8	40	42	42,5	25		19.529M32
M40x1,5	19 - 30	8	43	42	42,5	25		19.529M40
M50x1,5	25,5 - 37	9,5	55	52	50	10		19.536M50
M50x1,5	31 - 43	10	57	59	53	5		19.542M50
M63x1,5	35 - 48	11	65	64	55	5		19.548M63

* Klemmbereich der Zugentlastung

* Clamping range of anchorage