

TECHNISCHE DATEN:

Aufbau

Erweiterung	Messing CuZn39Pb3, galv. vernickelt
O-Ring	Nitrilkautschuk NBR
Außengewinde	metrisch, nach EN 60423
Innengewinde	metrisch, nach EN 60423

Eigenschaften

- Erweiterung einer Gewinde- oder Durchgangsbohrung auf eine größere Gewindegröße

Gruppen (Zone)	II 2 G (1, 2)	II 2 D (21, 22)
Kennzeichnung	Ex eb IIC Gb	Ex tb IIIC Db
Temperaturbereich	-40 °C / +85 °C	
Schutzart	IP66 / IP68 - 10 bar (30 min.)	
Prüfnorm	EN IEC 60079-0:2018, IEC 60079-0:2017 EN IEC 60079-7:2015+A1, IEC 60079-7:2017 EN 60079-31:2014, IEC 60079-31:2013	

EU-Prüfbescheinigung	PTB 16 ATEX 1006
IECEx-Zertifikat	IECEx PTB 16.0017

TECHNICAL DATA:

Configuration


Enlarger	Brass CuZn39Pb3, nickel-plated
O-ring	Nitrile rubber NBR
External thread	metric, as per EN 60423
Internal thread	metric, as per EN 60423

Properties

- enlarger for threaded or clearance holes to larger thread size

Group (Zone)	II 2 G (1, 2)	II 2 D (21, 22)
Marking	Ex eb IIC Gb	Ex tb IIIC Db
Temperature range	-40 °C / +85 °C	
Protection grade	IP66 / IP68 - 10 bar (30 min.)	
Test standard	EN IEC 60079-0:2018, IEC 60079-0:2017 EN IEC 60079-7:2015+A1, IEC 60079-7:2017 EN 60079-31:2014, IEC 60079-31:2013	

EU-Type Certificate	PTB 16 ATEX 1006
IECEx-Certificate	IECEx PTB 16.0017



Merkmale

Characteristics

A	B	L mm	tE mm	SW1 mm	H mm	Di mm		Art.-Nr. / Part No.
M12x1,5	M16x1,5	5	7	18	16	8	100	E102-11216-03-EX
M16x1,5	M20x1,5	5	7,5	22	16,5	12	100	E102-11620-03-EX
M20x1,5	M25x1,5	6	8	27	18,5	15	50	E102-12025-03-EX
M25x1,5	M32x1,5	7	9	34	20,5	21	25	E102-12532-03-EX
M32x1,5	M40x1,5	8	10	42	23,5	26	25	E102-13240-03-EX
M40x1,5	M50x1,5	8	13	52	30	34	10	E102-14050-03-EX
M50x1,5	M63x1,5	9	16	65	32,5	44	10	E102-15063-03-EX