

Anschlussklemmen, Steg

Feeding terminals, pin

Bornes de raccordement, pointes

						Ø			
Bestellnummer	Boden isoliert	Zuführung	Stegbreite	Steglänge	Anschluss- schrauben	ein-/mehr- drähtig	feindrähtig mit AE	A max./V max.	VPE
Article No.	Isolated base	Feeding	Pin width	Pin length	Connecting screws	single-/ multi wire	fine wire with sleeve	packing unit	
Référence	Sol isolé	Alimentation	Largeur pointe	Longueur pointe	Vis de rac- cordement	rigide monobrins/ rigide multibrins	souple avec embout	unité d'emballage	

Anschlussklemme, isoliert

Isolated terminals

Bornes de raccordement, isolées



802/130S	☐	längs lengthwise longitudinal	4 mm	32 mm	PZ2	6 - 25 mm ²	4 - 16mm ²	80 A AC 690V / DC 1000V	25
802/130SI	☒	längs lengthwise longitudinal	4 mm	32 mm	PZ2	6 - 25 mm ²	4 - 16mm ²	80 A AC 690V / DC 1000V	25
802/130S blau (blue / bleu)	☐	längs lengthwise longitudinal	4 mm	32 mm	PZ2	6 - 25 mm ²	4 - 16mm ²	80 A AC 690V / DC 1000V	25
802/130SI blau (blue / bleu)	☒	längs lengthwise longitudinal	4 mm	32 mm	PZ2	6 - 25 mm ²	4 - 16mm ²	80 A AC 690V / DC 1000V	25



802/130SQ	☐	quer across transversal	4 mm	32 mm	PZ2	6 - 25 mm ²	4 - 16mm ²	80 A AC 690V / DC 1000V	25
802/130SQI	☒	quer across transversal	4 mm	32 mm	PZ2	6 - 25 mm ²	4 - 16mm ²	80 A AC 690V / DC 1000V	25
802/130SQ blau (blue / bleu)	☐	quer across transversal	4 mm	32 mm	PZ2	6 - 25 mm ²	4 - 16mm ²	80 A AC 690V / DC 1000V	25
802/130SQI blau (blue / bleu)	☒	quer across transversal	4 mm	32 mm	PZ2	6 - 25 mm ²	4 - 16mm ²	80 A AC 690V / DC 1000V	25