




Part number		no. of contacts	A	B	C	D	E	F
1515 006 x401 xxx	6	2,54	6,96	8,06	5,76	4,76	8,89	
1515 008 x401 xxx	8	3,81	8,23	9,33	7,03	6,03	10,16	
1515 010 x401 xxx	10	5,08	9,50	10,6	8,30	7,30	11,43	
1515 012 x401 xxx	12	6,35	10,77	11,87	9,57	8,57	12,70	
1515 014 x401 xxx	14	7,62	12,04	13,14	10,84	9,84	13,97	
1515 016 x401 xxx	16	8,89	13,31	14,41	12,11	11,11	15,24	
1515 018 x401 xxx	18	10,16	14,58	15,68	13,38	12,38	16,51	
1515 020 x401 xxx	20	11,43	15,85	16,95	14,65	13,65	17,78	
1515 022 x401 xxx	22	12,70	17,12	18,22	15,92	14,92	19,05	
1515 024 x401 xxx	24	13,97	18,39	19,49	17,19	16,19	20,32	
1515 026 x401 xxx	26	15,24	19,66	20,76	18,46	17,46	21,59	
1515 028 x401 xxx	28	16,51	20,93	22,03	19,73	18,73	22,86	
1515 030 x401 xxx	30	17,78	22,20	23,3	21,00	20,00	24,13	
1515 032 x401 xxx	32	19,05	23,47	24,57	22,27	21,27	25,40	
1515 034 x401 xxx	34	20,32	24,74	25,84	23,54	22,54	26,67	
1515 036 x401 xxx	36	21,59	26,01	27,11	24,81	23,81	27,94	
1515 038 x401 xxx	38	22,86	27,28	28,38	26,08	25,08	29,21	
1515 040 x401 xxx	40	24,13	28,55	29,65	27,35	26,35	30,48	
1515 042 x401 xxx	42	25,40	29,82	30,92	28,62	27,62	31,75	
1515 044 x401 xxx	44	26,67	31,09	32,19	29,89	28,89	33,02	
1515 046 x401 xxx	46	27,94	32,36	33,46	31,16	30,16	34,29	
1515 048 x401 xxx	48	29,21	33,63	34,73	32,43	31,43	35,56	
1515 050 x401 xxx	50	30,48	34,90	36,00	33,70	32,70	36,83	
1515 052 x401 xxx	52	31,75	36,17	37,27	34,97	33,97	38,1	
1515 054 x401 xxx	54	33,02	37,44	38,54	36,24	35,24	39,37	
1515 056 x401 xxx	56	34,29	38,71	39,81	37,51	36,51	40,64	
1515 058 x401 xxx	58	35,56	39,98	41,08	38,78	37,78	41,91	
1515 060 x401 xxx	60	36,83	41,25	42,35	40,05	39,05	43,18	
1515 062 x401 xxx	62	38,10	42,52	43,62	41,32	40,32	44,45	
1515 064 x401 xxx	64	39,37	43,79	44,89	42,59	41,59	45,72	
1515 066 x401 xxx	66	40,64	45,06	46,16	43,86	42,86	46,99	
1515 068 x401 xxx	68	41,91	46,33	47,43	45,13	44,13	48,26	
1515 070 x401 xxx	70	43,18	47,60	48,7	46,40	45,40	49,53	
1515 072 x401 xxx	72	44,45	48,87	49,97	47,67	46,67	50,8	
1515 074 x401 xxx	74	45,72	50,14	51,24	48,94	47,94	52,07	
1515 076 x401 xxx	76	46,99	51,41	52,51	50,21	49,21	53,34	
1515 078 x401 xxx	78	48,26	52,68	53,78	51,48	50,48	54,61	
1515 080 x401 xxx	80	49,53	53,95	55,05	52,75	51,75	55,88	
1515 082 x401 xxx	82	50,80	55,22	56,32	54,02	53,02	57,15	
1515 084 x401 xxx	84	52,07	56,49	57,59	55,29	54,29	58,42	
1515 086 x401 xxx	86	53,34	57,76	58,86	56,56	55,56	59,69	
1515 088 x401 xxx	88	54,61	59,03	60,13	57,83	56,83	60,96	
1515 090 x401 xxx	90	55,88	60,30	61,4	59,10	58,10	62,23	
1515 092 x401 xxx	92	57,15	61,57	62,67	60,37	59,37	63,5	
1515 094 x401 xxx	94	58,42	62,84	63,94	61,64	60,64	64,77	
1515 096 x401 xxx	96	59,69	64,11	65,21	62,91	61,91	66,04	
1515 098 x401 xxx	98	60,96	65,38	66,48	64,18	63,18	67,31	
1515 100 x401 xxx	100	62,23	66,65	67,75	65,45	64,45	68,58	

Performance level	
2	PL1: >500 mating cycles
6	PL2: >250 mating cycles
5	min. 0,06µm Au over 0,7+0,2µm PdNi

Packaging	
tape & reel with 440pcs per reel	000
samples	333

Find further technical information on the drawing DS 15151210200

All Dimensions in mm Original Size DIN A3	Scale 5:1	Free size tol.	Ref.
All rights reserved Department EL PD	Created by ZHUANGJ	Inspected by LUOK	Standardisation ROEBEN
HARTING D-32339 Espelkamp	Title har-flex THR angled male connector	Date 08-Apr-2024	State 40 - Released
Type TB	Number 1515XXXX401XXX	Rev. H	Page 1/1