

Han Power T - 3 x Han Q 5/0



Image is for illustration purposes only. Please refer to product description.

Part number	09 12 008 4751
Specification	Han Power T - 3 x Han Q 5/0
HARTING eCatalogue	https://b2b.harting.com/09120084751

Identification

Category	Energy distributors
Series of hoods/housings	Han-Power® T
Element	Energy distributor
Specification	With 3x Han® Q 5/0 In Han® 3 A Housings, bulkhead mounting

Version

Number of contacts	4
PE contact	Yes

Technical characteristics

Rated current	16 A
Rated voltage conductor-earth	230 V
Rated voltage conductor-conductor	400 V
Rated impulse voltage	4 kV
Pollution degree	3
Rated voltage acc. to UL	600 V
Insulation resistance	$>10^8 \Omega$
Limiting temperature	-40 ... +125 °C
Mating cycles	≥ 500

Material properties

Material (contacts)	Copper alloy
---------------------	--------------



Pushing Performance

Material properties

Material (hood/housing)	Polyamide (PA)
Colour (hood/housing)	RAL 9005 (jet black)
Material (seal)	NBR
Material (locking)	Polyamide (PA)
Material flammability class acc. to UL 94	V-0
RoHS	compliant with exemption
RoHS exemptions	6(c): Copper alloy containing up to 4 % lead by weight
ELV status	compliant with exemption
China RoHS	50
REACH Annex XVII substances	No
REACH ANNEX XIV substances	No
REACH SVHC substances	Yes
REACH SVHC substances	Lead

Specifications and approvals

Specifications	EN 60664-1
	IEC 61984
UL / CSA	UL 2237 PVVA.E318390
	CSA-C22.2 No. 182.3 PVVA7.E318390
CE	Yes

Commercial data

Packaging size	1
Net weight	90 g
Country of origin	Germany
European customs tariff number	85366990
eCl@ss	27142409 Small distribution board