

## Han-Power T Q5/0 comp. assembled



Image is for illustration purposes only. Please refer to product description.

|                    |                                                                                       |
|--------------------|---------------------------------------------------------------------------------------|
| Part number        | 09 12 008 4753                                                                        |
| Specification      | Han-Power T Q5/0 comp. assembled                                                      |
| HARTING eCatalogue | <a href="https://b2b.harting.com/09120084753">https://b2b.harting.com/09120084753</a> |

### Identification

|                          |                                                               |
|--------------------------|---------------------------------------------------------------|
| Category                 | Energy distributors                                           |
| Series of hoods/housings | Han-Power® T                                                  |
| Element                  | Energy distributor                                            |
| Specification            | With 3x Han® Q 5/0<br>In Han® 3 A Housings, bulkhead mounting |

### Version

|                    |     |
|--------------------|-----|
| Number of contacts | 5   |
| PE contact         | Yes |

### Technical characteristics

|                                   |                 |
|-----------------------------------|-----------------|
| Rated current                     | 16 A            |
| Rated voltage conductor-earth     | 230 V           |
| Rated voltage conductor-conductor | 400 V           |
| Rated impulse voltage             | 4 kV            |
| Pollution degree                  | 3               |
| Rated voltage acc. to UL          | 600 V           |
| Insulation resistance             | $>10^8 \Omega$  |
| Limiting temperature              | -40 ... +125 °C |
| Mating cycles                     | $\geq 500$      |

### Material properties

|                     |              |
|---------------------|--------------|
| Material (contacts) | Copper alloy |
|---------------------|--------------|



Pushing Performance

## Material properties

|                                           |                                                        |
|-------------------------------------------|--------------------------------------------------------|
| Material (hood/housing)                   | Polyamide (PA)                                         |
| Colour (hood/housing)                     | RAL 9005 (jet black)                                   |
| Material (seal)                           | NBR                                                    |
| Material (locking)                        | Polyamide (PA)                                         |
| Material flammability class acc. to UL 94 | V-0                                                    |
| RoHS                                      | compliant with exemption                               |
| RoHS exemptions                           | 6(c): Copper alloy containing up to 4 % lead by weight |
| ELV status                                | compliant with exemption                               |
| China RoHS                                | 50                                                     |
| REACH Annex XVII substances               | No                                                     |
| REACH ANNEX XIV substances                | No                                                     |
| REACH SVHC substances                     | Yes                                                    |
| REACH SVHC substances                     | Lead                                                   |

## Specifications and approvals

|                |                         |
|----------------|-------------------------|
| Specifications | EN 60664-1<br>IEC 61984 |
| CE             | Yes                     |

## Commercial data

|                                |                                   |
|--------------------------------|-----------------------------------|
| Packaging size                 | 1                                 |
| Net weight                     | 89 g                              |
| Country of origin              | Germany                           |
| European customs tariff number | 85366990                          |
| eCl@ss                         | 27142409 Small distribution board |