

## Han Compact - GG - M25



Image is for illustration purposes only. Please refer to product description.

|                    |                                                                                       |
|--------------------|---------------------------------------------------------------------------------------|
| Part number        | 19 12 008 0426                                                                        |
| Specification      | Han Compact - GG - M25                                                                |
| HARTING eCatalogue | <a href="https://b2b.harting.com/19120080426">https://b2b.harting.com/19120080426</a> |

### Identification

|                             |                                                                                                        |
|-----------------------------|--------------------------------------------------------------------------------------------------------|
| Category                    | Hoods/Housings                                                                                         |
| Series of hoods/housings    | Han-Compact®                                                                                           |
| Type of hood/housing        | Hood                                                                                                   |
| Description of hood/housing | for standard cable gland<br>With separate PE terminating point<br>for all inserts of size Han-Compact® |

### Version

|                      |                                            |
|----------------------|--------------------------------------------|
| Locking type         | Single locking lever                       |
| Size                 | Han-Compact®                               |
| Version              | Top entry                                  |
| Cable entry          | 1x M25                                     |
| Field of application | Hoods/housings for industrial applications |

### Technical characteristics

|                                        |                 |
|----------------------------------------|-----------------|
| Limiting temperature                   | -40 ... +125 °C |
| Degree of protection acc. to IEC 60529 | IP65            |
| Type rating acc. to UL 50 / UL 50E     | 12              |

### Material properties

|                         |                      |
|-------------------------|----------------------|
| Material (hood/housing) | Zinc die-cast        |
| Surface (hood/housing)  | Powder-coated        |
| Colour (hood/housing)   | RAL 9005 (jet black) |



Pushing Performance

## Material properties

|                             |           |
|-----------------------------|-----------|
| RoHS                        | compliant |
| ELV status                  | compliant |
| China RoHS                  | e         |
| REACH Annex XVII substances | No        |
| REACH ANNEX XIV substances  | No        |
| REACH SVHC substances       | No        |

## Specifications and approvals

|           |                                   |
|-----------|-----------------------------------|
| Approvals | DNV GL                            |
| UL / CSA  | UL 1977 ECBT2.E235076             |
|           | UL 2237 PVVA2.E318390             |
|           | CSA-C22.2 No. 182.3 ECBT8.E235076 |
|           | CSA-C22.2 No. 182.3 PVVA8.E318390 |
| CE        | Yes                               |

## Commercial data

|                                |                                          |
|--------------------------------|------------------------------------------|
| Packaging size                 | 1                                        |
| Net weight                     | 260 g                                    |
| Country of origin              | Germany                                  |
| European customs tariff number | 85389099                                 |
| eCl@ss                         | 27440202 Shell for industrial connectors |