

RADIO 433,920 MHz

[Transmitters]

AUTOMATION

SLIM+



The latest development in the SLIM series, **SLIM+** includes a new technology enabling encrypted and protected* transmission (encryption AES128).

- ▶ Reinforced housing, matt black, metal contour lines and white details
- ▶ 4 channels, Rolling code
- ▶ XP and RW+ features : radio programming using GT+ (see p.54-55) without opening the blister
- ▶ Encrypted and protected transmission (AES128)
- ▶ Sequential numbers
- ▶ Rated range : 150 m* free field
- ▶ Battery-saving feature

TECHNICAL SPECIFICATIONS

Power supply :	1 lithium battery 3V (CR2032 type)
Frequency :	433,920 MHz
Nr. channels :	4
Indicators :	1 red LED
Size and weight :	29 x 65 x 11 mm - 27 g



* on supported PRASTEL receivers

SLIM2E SLIM4E



With its **stylish, plain and lightweight** design, **SLIM** can be used on all existing PRASTEL 433,920 MHz installations, combined with all our 433,920 MHz transmitters.

- ▶ Modern, innovative and stylish design : shiny white housing with metal contour lines and chrome-plated details
- ▶ Rolling code
- ▶ XP and RW+ features : radio programming using GT+ (see p.54-55) without opening the blister
- ▶ Sequential numbers
- ▶ Rated range : 100 m* free field
- ▶ Battery-saving feature
- ▶ Available with dual technology :

SLIM4E-DT : radio 433 MHz + proximity 125 KHz

SLIM4E-MF : radio 433 MHz + prox. Mifare® 13,56 MHz

TECHNICAL SPECIFICATIONS

Power supply :	1 lithium battery 3V (type CR2032)
Frequency :	433,920 MHz
Nr. channels :	2 for SLIM2E 4 for SLIM4E
Indicators :	1 white LED
Size and weight :	28 x 56 x 12 mm - 22 g