

ECSH12080

HALOGEN FREE SLOTTED TRUNKING WITH COVER 4/6/4 DIM. 120X80



Trunkings > Panelboards systems > Cable management >
Slotted trunkings halogen free > Slotted cable trunking > Light
grey - type s - narrow slots 4/6/4



IMMAGINE
RAPPRESENTATIVA



REPRESENTATIVE
IMAGE

Technical Symbols/Marks/Approvals

HF	UL94 V2	GWT 960°	-25°	+90°	CE	RoHS II	MADE IN ITALY
----	------------	-------------	------	------	----	---------	---------------------

Norms

EN 50267-2-1 EN 50267-2-2 IEC 60754-1 IEC 60754-2 EN 50085-1

EN 50085-2-3 UL 1565

Description

Slotted trunking made of halogen free tecnopolymer. Self-extinguishing according to the Standard UL94 - V2 at 1,6 mm. Resistance to abnormal heat: up to 960°C (GWT). Dimensione stability between -25°C and +90°C. FPerforated bottom according to the Standard DIN 43659. Second break line at the base of the slots permits to remove the whole trunking wall (with tool).


Etim

GROUP EG000007 - Slotted cable trunking system

CLASS EC000012 - Slotted cable trunking system

Material	Other	Halogen free	Yes	Colour	Grey
Type of fastening	Bottom perforation	Width	120 mm	Height	80 mm
Length	2 m	Distance of slots	6 mm	Slit width	4 mm
Type of side wall	Hole-/slot punching	Self-extinguishing	Yes	Flexible	No
Usable cross section	8640 mm ²	With cover	Yes	RAL-number	7035

Documentation available for download



Barcode



8054320286264

Cardboard

16 MT

0.26x0.18x2.027 [m]

12.5008 [kg]



8055035960548

Pallet

288 MT

1.2x0.8x2.2 [m]

225.0144 [kg]