

Jack Bulkhead

Bulkhead, 8.5W/15W, 1050/1850lm, 120lm/W, 3 CCT
2700/3000/4000K, IP54, On/Off, White, Emergency

ID: 0028920261


GTIN: 7630268419844

5 YEARS *
WARRANTY



Technical Data

Rated luminous flux according to IEC 62722-2-1:	1050...0 lm
Luminaire efficacy:	120...0 lm/W
Colour temperature:	2700...4000 K
Colour rendering index CRI:	80-89
Colour consistency (McAdam ellipse):	SDCM4
Unified Glare Ratio (UGR):	26
Beam angle:	> 80° - Extreme wide beam
Light distributor:	Diffuser lens/optic/panel
Energy efficiency class of the light source according to EU regulation 2019/2015:	C
Protection class according to IEC 61140:	II
Nominal voltage:	220...240 V
Nominal current:	43...78 mA
Max. system power:	18 W
Power factor:	0.8
Max. number of luminaires per miniature circuit breaker B16 (MCB):	30
Max. number of luminaires per miniature circuit breaker C16 (MCB):	50
Connection type:	Push-in clamp
Rated lifetime L70/B50 at 25 °C:	60000 h
Impact strength:	IK08
Rated ambient temperature according to IEC 62722-2-1:	0...40 °C
Filament test according to IEC 60695-2-11:	850 °C - 30 s
Photobiological safety according to EN 62471:	RG0
Covering of the luminaire with thermally insulating material possible:	no
Housing material:	Plastic
Housing colour:	White
Height/depth:	52 mm
Outer diameter:	280 mm
Suitable for emergency lighting:	yes
With movement sensor:	no
With light sensor:	no
With control gear:	yes



LUMINOUS INTENSITY DISTRIBUTION

