
Jack

Bulkhead,8.5/15W,1020/1850lm,123lm/W,3 CCT 2700K+ 3000K+4000K,IP54,On/Off,White,MW Corridor Sensor

Model No.:
SGSO Sku: **0028920234**
GTIN/EAN: **7630268419080**

Suitable for wall mounting:	Yes
Suitable for ceiling mounting:	Yes
Suitable for surface mounting:	Yes
Lamp type:	LED not exchangeable
Housing material:	Plastic
Surface protection housing:	Untreated
Housing colour:	White
Material cover:	Plastic, opal
Type of grid:	None
Voltage type:	AC
Nominal voltage:	220 ... 240 V
Nominal current:	40 ... 69 mA
Type of control gear:	LED operating device current-controlled
No dim function:	Yes
Light distributor:	Diffuser lens/optic/panel
Light sharing:	Symmetric
Beam angle:	Extreme wide beam >80°
Colour consistency (McAdam ellipse):	SDCM4
Light outlet:	Indirect
Energy efficiency class of the light source according to EU regulation 2019/2015:	C
Rated life time L70/B50 at 25 °C:	60000 h
Max. number of luminaires per miniature circuit breaker B 16 (MCB):	23
Max. number of luminaires per miniature circuit breaker C 16 (MCB):	38
Degree of protection (IP):	IP54
Degree of protection (NEMA):	Other
Impact strength:	IK08
Protection class:	II
Rated ambient temperature according to IEC 62722-2-1:	-20 ... 45 °C
With movement sensor:	Yes
Filament test according to IEC 60695-2-11:	750 °C - 30 s
Suitable for lamp power:	8.3 ... 14.9 W
Max. system power:	14.9 W
Luminaire efficacy:	120 lm/W
Rated luminous flux according to IEC 62722-2-1:	1850 lm
Colour of light:	White
Colour temperature:	2700 ... 4000 K
Flickering value Pst LM:	0
Colour rendering index CRI:	80-89
Power factor:	0.9
Stroboscope effect value SVM:	0.4
Width:	280 mm
Height/depth:	52 mm
Length:	280 mm
Outer diameter:	280 mm
Type of wiring:	Ending
Number of poles:	2
Conductor cross section:	0.5 mm^2
Connection type:	Push-in clamp
Total harmonic distortion:	15
Photobiological safety according to EN 62471:	RG0
Unified Glare Ratio (UGR):	26
Colour of light adjustable:	Positions





LUMINOUS INTENSITY DISTRIBUTION

