



KING Bulkhead

11/16/21W,1000lm/1500lm/2000lm, 95lm/W,3 CCT
3000K/4000K/6500K,IP66,MW Sensor,White

ID: 0028920257

GTIN: 7630268419837

5 YEARS *
WARRANTY



Technical Data

Rated luminous flux according to IEC 62722-2- 1:	1000/1500/2000
Luminaire efficacy:	95...0 lm/W
Colour temperature:	3000...6500 K
Colour rendering index CRI:	80-89
Colour consistency (McAdam ellipse):	SDCM4
Unified Glare Ratio (UGR):	35
Beam angle:	> 80° - Extreme wide beam
Light distributor:	Diffuser lens/optic/panel
Energy efficiency class of the light source according to EU regulation 2019/2015:	D
Protection class according to IEC 61140:	II
Nominal voltage:	220...240 V
Nominal current:	65...105 mA
Max. system power:	21 W
Power factor:	0.75
Max. number of luminaires per miniature circuit breaker B16 (MCB):	41
Max. number of luminaires per miniature circuit breaker C16 (MCB):	45
Connection type:	Push-in clamp
Rated lifetime L70/B50 at 25 °C:	100000 h
Impact strength:	IK10
Rated ambient temperature according to IEC 62722-2-1:	-20...50 °C
Filament test according to IEC 60695-2-11:	750 °C - 30 s
Photobiological safety according to EN 62471:	RG0
Covering of the luminaire with thermally insulating material possible:	no
Housing material:	Plastic
Height/depth:	75 mm
Outer diameter:	300 mm
Suitable for emergency lighting:	no
With movement sensor:	yes
With light sensor:	no
With control gear:	yes
Type of control gear:	LED operating device voltage-con- trolled
Light distribution:	Symmetric
Type of wiring:	Ending
Flickering value Pst LM:	1

