



Taso 0.5m Kitchen luminaire

7W, IP21, IK06, 2 CCT 3000K+4000K, 770lm, 110lm/W,
On/Off, White

ID: 0028920258

GTIN: 7630268419851

5 YEARS *
WARRANTY



Technical Data

Rated luminous flux according to IEC 62722-2-1:	770...0 lm
Luminaire efficacy:	110...0 lm/W
Colour temperature:	3000...4000 K
Colour rendering index CRI:	80-89
Colour consistency (McAdam ellipse):	SDCM3
Unified Glare Ratio (UGR):	25
Light distributor:	Diffuser lens/optic/panel
Energy efficiency class of the light source according to EU regulation 2019/2015:	E
Protection class according to IEC 61140:	I
Nominal voltage:	220...240 V
Nominal current:	65...65 mA
Max. system power:	7 W
Power factor:	0.9
Connection type:	Push-in clamp
Rated lifetime L70/B50 at 25 °C:	100000 h
Impact strength:	IK06
Rated ambient temperature according to IEC 62722-2-1:	-20...40 °C
Filament test according to IEC 60695-2-11:	650 °C - 30 s
Photobiological safety according to EN 62471:	RG1
Covering of the luminaire with thermally insulating material possible:	no
Housing material:	Steel
Length:	550 mm
Width:	74 mm
Height/depth:	49 mm
Suitable for emergency lighting:	no
With movement sensor:	no
With light sensor:	no
With control gear:	yes
Type of control gear:	LED operating device current-controlled
Light distribution:	Symmetric
Type of wiring:	Suitable for loop-through wiring
Flickering value Pst LM:	1
Stroboscope effect value SVM:	0.4
Total harmonic distortion (THD):	0.2 %

