

KEY-K01, KEY-KP01 and KEY-KPZ01 Keypads



As well as having a modern, small and discreet design the KEY-K01, KEY-KP01 and KEY-KPZ01 have a choice of prox, non-prox or prox with zones.

The prox keypads have connections for an external prox reader to be connected in addition to the internal prox. To add greater flexibility to the KEY-KPZ01 you can select the option of having two zones on board for an even faster connection of zones.

At a glance...

- A navigation key for easy access to the user and installer menus
- A status LED that can be turned on or off from within the keypad menu
- An internal prox reader (not available on the KEY-K01)
- Built in panic button enabled in programming
- One programmable transistroided output (KEY-KPZ01 Only)
- External prox reader connections, KEY-EP (Not available on KEY-K01)

Product specification

Compliance	PD6662:2017 Grade 2 or Grade 3, BS8243:2010, EN50131-1:2006+A1:2009 Grade 2 or Grade 3, EN50131-3
Zones	2 zones available on the KEYKPZ01 only
Proximity reader	Built in prox (Not available on the KEY-K01)
Dimensions	Keypad: 128 x 128 x 29mm
Weight	0.2kg
Temperature range	Environmental class 2 -10°C to 55°C @ 75% RH
One transistorised output	Available on KEY-KPZ01 only

Compatible products

i-on16/ EUR	Panel end station
i-on30EX/ EXEUR	Panel end station
i-on40/ EUR	Panel end station
i-on50EX/ EXEUR	Panel end station
i-on160EX/ EXEUR	Panel end station
Menvier30KPZ	Panel end station
Menvier40KPZ	Panel end station
Menvier100KPZ	Panel end station
Menvier300KPZ	Panel end station
Multibus	Panel end station